



<T.K.> <Pneumatic Tool Oil>

DESCRIPTION

LOFGE T.K. multi-function impact-type of pneumatic tool oils are made up of refined mineral oil and water-proof, rust-proof, anti-sludge and anti-wear, anti-oxidation, anti-foam additives. It satisfy special requirements of lubrication for a variety of pneumatic tools (including work under the worst conditions of the impact-type pneumatic tools).

Meets: ISO 6743/11 CLASS P

APPLICATION

- ★For lubrication of high-performance rock drilling air hammer.
- ★For online lubrication of pneumatic tools, pneumatic rock drill for enclosed space. (such as: mines, tunnels, etc).

FEATURE

- Superior oxidation stability, control of oil oxidation.
- Good anti-foam performance and to provide reliable protection for lubrication.
- Rust-proof, anti-wear, giving full play to the tools of performance, extend tool life.

TYPICAL SPECIFICATION

LOFGE T.K.	UNITS	10	22	32	37	46	68	100
(15°C) Density	Kg/m ³	0.871	0.871	0.872	0.872	0.876	0.883	0.890
(40°C) Viscosity	mm ² /s	10	22	32	37	46	68	100
(100°C)		2.6	4.2	5.1	6.0	6.8	8.8	11.5
Viscosity Index	-	103	103	103	103	103	102	102
Flash Point	°C	170	179	198	232	243	252	260
Pour Point	°C	-24	-30	-30	-30	-30	-30	-24

The typical specification mentioned represent mean values.