



<TF> <Anti-rust Greases>

DESCRIPTION

LOFGE TF anti-rust greases are composed by the selection of mineral base oil, lithium soap thickener, anti-rust agent additive. Dedicated to all types of machine tools and various metal products, rust-proof long-term conservation.

APPLICATION

- ★Brush: at room temperature, brush the surface to form into a continuous film. Also can be used for hot dip-coating the work piece, but heating oil temperature not exceed 80°C, in order to avoid metamorphism.
- ★Clean out: removed by hydrocarbon solvents (Industrial gasoline or kerosene lamp).
- ★Applicable to brushing all kinds of machine tools and various metal products(in particular cast iron products) of rust-proof long-term conservation, retention period at more than three years for packing steel pieces, excellent anti-corrosion effect for copper and copper alloy.

FEATURE

- Excellent anti-rust qualities, under normal circumstances antirust period of up to 2~3 years.
- Good coating, soft, brushing in winter and summer.
- It has good cold-heat resistance, slip temperature is higher than 55°C, indurations temperature less than -60 °C.
- Good adhesiveness, and the removal of convenience.
- Grease are transparent, easy to check the products at the antirust period.

TYPICAL SPECIFICATION

LOFGE TF	UNITS	1	2
Color	-	Brown	Brown
(25°C) Penetration Worked	0.1mm	310~340	265~295
Average Dropping Point	°C	170	180
Anti-Rust (in door)	year	2	3

The typical specification mentioned represent mean values.